

# Declare.

## Biform Wood Plastic Composite Biform Ltd

**Final Assembly:** Auckland, New Zealand

**Life Expectancy:** 50 Year(s)

**End of Life Options:** Salvageable/Reusable in its Entirety,  
Landfill (100%)

### Ingredients:

Poplar Wood Fibre; Polyethylene; Talc; 2,5-Furandione, polymer with ethene; C.I. Pigment Yellow 42; Carbon black; Diiron Trioxide; Titanium dioxide; Octadecanamide, N,N'-1,2-ethanediybis-; Octadecanoic acid, zinc salt; Paraffin waxes and Hydrocarbon waxes, oxidized, calcium salts; 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidiny)-, polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products with 2,4,4-trimethyl-2-pentanamine; Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester; 3-Isothiazolinone

### Living Building Challenge Criteria:

#### I-13 Red List:

- LBC Red List Free      % Disclosed: 100% at 100ppm
- LBC Red List Approved      VOC Content: Not Applicable
- Declared

**I-10 Interior Performance:** Not Applicable

**I-14 Responsible Sourcing:** Not Compliant

BFM-0001  
EXP. 01 JAN 2025  
Original Issue Date: 2023